

KUMAR AUDIOSAUDIO POWER AMPLIFIER MODULE

KA 2421 BRIDGED MONO MODULE

FEATURES:

- *High Power Bridged Audio Amplifier Module.
- *User Friendly Design.
- *With Heavy Heat sink to dissipate Heat Properly.
- *Class AB Classification.
- *Four Output Power Transistor drivers (Complimentary Pairs).
- *Used High Quality Genuine Components for best performance.
- *Passed Three stages of Quality control test.

SPECIFICATIONS:

S.NO	PARAMETER	RATINGS
1	Operating Voltage range DC	<u>+</u> 35V DC to <u>+</u> 45V DC
2	Recommended Operating Voltage DC	<u>+</u> 42V DC
3	Input Impedance	56K Ohms
4	Output Power RMS (R∟=4 Ohms)	220 W
5	Output Power RMS (RL=8 Ohms)	130 W
6	Maximum Temperature Withstand	125°C
7	Total Harmonic Distortion (THD) at 10W	0.04% (f=1KHz,R _L =8 Ohms)
8	Recommended Output Load	$R_L \ge 4 \text{ Ohms}$ $R_L < 4 \text{ Ohms is NA}$
9	Frequency Response	15Hz to 30KHz
10	Classification	Class AB

Note: This product is only for Professional technicians and it is a non-serviceable product.